



After Installation clean up and final system test.

Clean-Up:

1. Remove all construction residue and foreign materials. Wipe unit clean with a damp rag, otherwise, staining may occur.
2. Plaster drops may be removed by applying pressure with the edge of a piece of wood or plastic putty knife. **Do Not** use metal scraper. For spots left by plaster or grout: rub lightly with a liquid detergent on a damp cloth or sponge.
3. **Do Not** use abrasive cleaners, scouring powders, steel wool, wire brushes, or anything else that may harm or dull the surface.
4. Paint, tar or stubborn stains may be removed with acetone (fingernail polish remover), turpentine or rubbing alcohol. To avoid discoloration, cleaners containing petroleum distillates must not remain on surface. **Never** use lacquer thinner or chlorinated solvents.
5. Dulled areas can be restored to a high gloss with white or cream colored automotive rubbing compound, followed by application of carnauba wax or white or cream automotive paste wax and buffing.
6. Remove minor scratches with 600grit wet/dry sandpaper, followed by use of automotive rubbing compound and paste wax, as above.
7. Major gouges require professional repair.

System Test:

1. Dirt left in tub may cause staining. Remove all debris before filling. Fill clean tub with water to overflow fitting.
2. To test the Ground Fault Circuit Interrupter (GCFI), push the test button. The GCFI should interrupt power. Push the reset button. Power should be restored. If the GCFI fails to operate in this manner, there is a ground current flowing, indicating the possibility of an electric shock. Do not use this unit. Disconnect the unit and have the problem corrected by a licensed electrician before using.
3. Run the whirlpool through its entire time cycle (20 Minutes) using every possible function on the control panel according to the Operation and Maintenance Guide.
4. If any electrical malfunctions occur, consult electrician. Malfunctions of the pump, whirlpool controls or the circulation system should be reported back to Trajet Products, Inc.
5. Through access panel, check for leaks in whirlpool plumbing system. Make sure unions on pump are hand tight.
If leakage is occurring at any other point, notify Trajet Products, Inc immediately.
6. Empty whirlpool completely by allowing self-draining components to empty. Wipe dry.